



## ООО «Никелид»

Условный проход		Наружный диаметр			
Ду	Ду	DIN	SMS	ISO	ГОСТ
5	1/8"	—	—	10,3	—
8	1/4"	—	6,35	13,7	—
10	3/8"	12	9,54	17,1	14
15	1/2"	18	12,7	21,3	18
20	3/4"	22 (23)	19,05	26,9	20
25	1"	28	25	33,7	32
32	1 1/4"	34 (35)	31,75	42,4	38
40	1 1/2"	40 (43)	38	48,3	45
50	2"	52 (53)	50,8	60,3	57
65	2 1/2"	70	63,5	76,1	76
80	3"	84 (85)	76,1	88,9	89
100	4"	104	101,6	114,3	108
125	5"	129	129	139,7	133
150	6"	154	154	168,3	159
200	8"	204	204	219,1	219
250	10"	254	254	273	273
300	12"	—	—	323,9	325
350	14"	—	—	355,6	377
400	16"	—	—	406,4	426
500	20"	—	—	508	530
600	24"	—	—	609,6	630
700	28"	—	—	711,2	720
800	32"	—	—	812	820
900	36"	—	—	—	920
1000	40"	—	—	—	1020
1200	48"	—	—	—	1220
1400	56"	—	—	—	1420
1600	64"	—	—	—	1620
1800	72"	—	—	—	1820
2000	80"	—	—	—	2020
2200	88"	—	—	—	2220
2400	96"	—	—	—	2420